





# Specifying guide

				
<b>SPECIFICATION</b>	<b>NSC9PRO</b>	<b>NSC11PRO</b>	<b>NSC14PRO</b>	<b>NSC4218</b>
Total height (mm)	527	654	822	1220
Total depth with connectors (mm)	532	532	532	650
Width (mm)	302	302	302	432
Drain height (mm)	465	580	745	1115
Overflow height (mm)	245	320	465	690
Max daytime working pressure (bar)	8.5	8.5	8.5	8.5
Min daytime working pressure (bar)	1.3	1.3	1.3	1.3
Inlet/outlet connections	22mm push-fit	22mm push-fit	22mm push-fit	1" BSP male
Drain/overflow connections	3/8" hose spigot	3/8" hose spigot	3/8" hose spigot	1/2" hose spigot
Electrical supply via transformer	24V 50Hz	24V 50Hz	24V 50Hz	24V 50Hz
Salt storage capacity (kg)	24	34	45	91
Maximum softened water capacity at 300ppm (litres)	1635	2068	3436	9094
Model recommendation based on household size <sup>^</sup> (based on usage per person of 140 litres per day at 300ppm)	1-5 people	1-7 people	1-9 people	9+ people

<sup>^</sup> Water hardness and flow rates can affect which model is right for you.

As part of our policy of on-going research and development, Tapworks reserves the right to alter design and specification without notice.

To view our complete range of water softeners visit [www.tapworks.co.uk](http://www.tapworks.co.uk) or give us a call today on **01494 480 621**

**TAPWORKS**  
WATER SOFTENERS

[www.tapworks.co.uk](http://www.tapworks.co.uk)



A Marmon |  
Berkshire Hathaway  
Company